

Model: Nx 32





BREAK FREE WITH A SOFTWARE BASED PBX





CALL4TEL NX32 DIAGRAM - CONNECTION PROCEDURE



On this topic

- Step 1: Web Access
- Step 2: IP Configuration
- Step 3: Allow IP in Firewall
- Step 4: SIP Connect Allow static route
- Step 5: 3CX Licensing
- Step 6: Configure SBC
- Step 7: Profile
- Step 8: Need to change Password?
- Step 9: On new version available
- Step 10: After Update
- Step 11: Indicators and Beepers

01 Web Access

1.1 URL



1.2 To Access device

	 Connect WAN to DHCP Network WAN gets the IP from DHCP Network to find IP. Download
WAN	Call4tel NX Detector tool in the link below. Download Link: http://update.call4tel.com/detector/NX32_DETECTOR.zip
	Once the IP address found proceed with URL: URL: http:// <your ip="">:5448</your>
	Mandatory: Set the WAN IP (the one which is connected to the internet and the network with all the phones) to be static.
LAN	http://192.168.101.1:5448

- 1.3 Connect the WAN port to your Switch or Router, using the (included) network cable.
- 1.4 **URL:** http://<your ip>:5448

1.5 Enter username & password Username : root Password : 3cx

Upername	
Partanet	
Login	- 3

02 IP Configuration

LAN

- 2.1 By default, "**Obtain IP address automatically**" will be enabled and the system will obtain IP address automatically.
- 2.2 By selecting "Use the following IP address", the system will be enabled to update a custom LAN IP Address.



WAN

- 2.3 By default, "Use the following IP address", the system will be enabled to update custom WAN IP Address.
- 2.4 By selecting "**Obtain IP address automatically**" the system will obtain an IP address automatically.

WAN	Address 🔲 📰 🌅
And A DECEMBER OF	Hetmask 🔛 🔛 🔛
	Gateway 📄 📄 🛑

DNS Information

By default "DNS" will be obtained automatically. 2.5



03 Allow IP in Firewall

You can allow IP in Firewall (External access for port 5448) by selecting any one option

Allow All:	Allow all ip address
Allow IP:	Allow only specific ip address
Allow IP Range:	Allow specific ip address with range
Firewall changes:	Can delete IP address added



A www.call4tel.com

04 SIP Connect - Allow static route

If you need to add a Static route, select "Static route" to update

Allow IP: Allow only specific ip address with either LAN or WAN

Allow IP Range: Allow specific ip address in range either LAN or WAN

	FIREWA	LL SIP CON	NECT 3CX	WARRANTY	CONTACT US	-
Static Route						
Allow IP	- A	llow IP Range				
Lan	O v	Van				
Destinatio	on IP					
(SIP Serve	n) (OR)				
)	
					2	

Need to delete IP Address added?

Click on delete button in "Route Changes" to delete the record





05 3CX Licensing

Are you planning to install or reset 3CX and network?

Latest 3CX Version:	Show 3CX latest version
3CX Uninstall:	Click to uninstall 3CX
Call4tel Reset:	Click to reset call4tel NX device
Network Reset:	Click to reset network
3CX Wizard Reset:	Click to reset 3CX
Reset All:	Click to reset all settings
Power off:	Click to Switch off your device
Reboot:	Click to Reboot your device



Need to check your 3CX version?

At all-times, the installed 3CX version will be displayed here.



06 Configure SBC

Are you planning to change 3CX to SBC?

Select SBC and then click "Change" to change device from 3CX to SBC



Fill SBC Form and then click "Confirm" to change device from 3CX to SBC

SBC Form	
Please enter your 3CX SBC details	Í
SCK SBC Paseword	I
SCX Web Url	
3CX SBC Authentication Key Id	ł
a	-
Contirm Cancel	

After updating from 3CX to SBC, you can update SBC settings as follows:

Call4tel Reset:	Click to reset call4tel NX device
Network Reset:	Click to reset network
Reset All:	Click to reset all settings
Power off:	Click to Switch off your device
Reboot:	Click to Reboot your device
SBC Uninstall:	Click to uninstall SBC
SBC Config Update:	Click to update SBC Config





08 Need to change Password?

Enter current and new password and then click "Change Password"

User name : root	
Current Password	
New Password	
	9

09 New version available

You will be notified once a new version is available. You can update by clicking the "click here" button



[+65 6340 1005

10 After update

Once the update is complete, you will be notified that "Your device is up to date".



11 Indicators and Beepers

- a. When the power source is connected, you will hear a short beep which means, the system is powered up.
- b. When the system is started and ready, you will hear a long beep.
- c. A long press on RST button for 2-3 seconds and release, will ensure the system is powered off. You will hear four beeps as confirmation. The system is now successfully powered off.
- d. For reset a long press on RST for maximum 8 seconds until you hear ten rapid beeps, resets the 3CX phone system & network settings and auto reboots to a fresh installation. Proceed to use the default IP address to access the setup interface.
- e. If the 12V power is disconnected or there is a sudden outage, the UPS battery residing inside is automatically triggered & executes the "**Power-off**" command to shut down the system safely, avoiding any data loss or system damage.

Additional Guide

Call4tel NX32 Detector: To detect a connected NX32 device in your network, click here to download

Scan				
ý.	Nothers	SOC Address	Web Access	Action CLUX HERE
i - A	SURFRIEX	2	1	CLOKHERS



How to obtain a License Key?

Step: 1 In order to get your 3CX license key, you need to fill in the form below and click the submit button to register your account.

URL: https://www.call4tel.com/activation/

	Activation	
ara-w	Science 11	
	(TREAMER)	
Gen :	(74+8)a/2	
Sko. P	a(b)w/	
w,	477.7	
1.8C	12K3K2	
inclasta C		

Step: 2 You will receive an email to confirm your email address.



Step: 3 Go to the Call4tel portal login area and enter your Username and Password and then click Login. **URL:** https://erp.cal4care.com/nx32/

User Nar	ne	
å	1.54.1.307.0	
Passwor	d .	
A	Pacawer of	
	COSIN	



Step: 4 You can find the list of Licenses on the License Details page. In that window, click the **"Add new"** button to register a new license.

hform	ation that						0 - 3
6	Markey	5					
	5.00	Junia Ro.	MMC address 1	MAC objects	-Laune	Analmint	Auton
-	Ϋ́.	14252245	00-14-23-04-23-45	57-0-46-87-05-10	3000-47494727	100	Harris
ш							
11	8	42334545	02-14-25-04-24-45	02-85-46-62-00-20	2200-020-0777	100 m	lippinels

Step: 5 Enter your device serial number and mac address and click the "Get new license key".

Add New	Þ
Enter Serial Number	
Enter MAC Address 1	
Enter MAC Address 2	
	Get New License Key
	Close

Step: 6 You will receive an email with your 3CX License details.

How to upgrade your License Key?

Step: 1 Go to the Call4tel portal login area and enter your username and password and click the "**Login**" button. **URL:** https://erp.cal4care.com/nx32/

1	call4te	
Over Na	-	
â	11 M - 16 M -	
Passwor	d	
8	PO WWWWIT	
	INDIA	

Step: 2 You can find the list of License keys here. Click the "Upgrade" button to upgrade your license.

ase	Details	9					Silway P
iti m	etice Life						11 (* 3
-0	-						
	111	Seriel Sec.	allCastrin I	and entropy (LINETH	- Million and	-
•	1m 1	Territte. 14/0/845	also anten 1 16/4 (Jan 2041	1000-000001 (0.44-00-01-00-00	aneggedin		
	100 1 2	14/03/845	96-14-22-08-25-45	(0.6446-0.6538	monthletin	UL.	

Step: 3 Select your available license and choose desired upgrade and then click "Add to cart" button.

cense Upgrade			€70are +Capital
Cheselfor .			10 it
Course the to	appointe an el tractore -	1983	
Lionac N.S.			
Editor	Assessed	1945	
Simularizous Gal	TWEEKK		
	THE REPORT		

Step: 4 In the Cart Page you can see the upgrade details that you selected. After confirmation, click the "**Proceed**" button to progress to the payment page..

					The set \$1500	
1	8.05	$\mathcal{D}(\mathcal{H}) = \mathcal{D}_{\mathcal{H}} \oplus \mathcal{D}_{\mathcal{H}} \oplus \mathcal{D}_{\mathcal{H}} \oplus \mathcal{D}_{\mathcal{H}} \mathcal{D}_{\mathcal{H}} \oplus D$	11205.15		2020	16310
1	6.59	Copies Haw 2010 Factor Probability (Copies Haw 2010) COCCUSTS and Copies	1844414	8	MV3 8	1863.14
4	6.57	they as derived in a close of the second texture allocations around strengther of the	ip-ais.	1	W.Y.W	tatia.is
					H-1 Te at	INT-IN CL
					100.100.00	÷
					Continue	Notes to

Step: 5 Choose payment method and click the "**Proceed**" button to pay.

0.0	rt vori lit						40-
	-	(market)		(1946-000a)	ŵ		and the set
10	.28.	ALCONTAGE SPREAD.	NORS-COMP	1547.8	10	1.025	9m29
¢.	100	$\begin{array}{l} F(g_{1},g_{2}) \in \mathcal{F}^{\infty}_{2}(\mathcal{F}) \cong \mathcal{F}^{\infty}_{2}(\mathcal{F}) \otimes \mathcal{F}^{$		1662.3		6.12.2	1895.3
	3.74	Neg averaging the expansion and the control constants of		·32112	¥2	e	*min.*#
						1.11.11.02	Sec. All
						$\mathbf{r} \sim_{\mathbf{s}} \mathbf{e}^{-1/(1+\varepsilon)}$	3
						(anysika)	(K)
						Two offensives	3
							1880 B
	27	es mens Tarins					
	1	lauper lace	-mrvs.s	osan -			
	in an a	been wrond					
	CNER	t or Debit Carta (Fig.Fig.)	100	Credit	Const > De	bit Card	
	Via			VI	SA		

Step: 6 You will receive an email with your 3CX License details.