

## Uploading the Call4tel FXS Template to 3CX

0

- 1. Download the Call4TelNXS-ZIP File from <u>here</u> (Make sure to extract All Files).
- 2. Change the Call4Tel XML file owner name from root to phonesystem as shown below:

👔 🚰 Download 🔹 🎢 Edit 🔹 🗙 🛃 🌆 Properties 🔛 New 🔹 🗌	Cali4telNXS2-2EXS.fxs.xml, Properties ?
/var/lib/3cxpbx/Instance1/Data/Http/Templates/fxs/	Common Chediaum
Name	6 Res
L n Call4telNXS2-2FXS.fxs.xml Call4telNXS4-4FXS.fxs.xml Call4telNXS8-8FXS.fxs.xml Call4telNXS12-12FXS.fxs.xml Call4telNXS24-24FXS.fxs.xml	Location: //3cxpbx/Instance1/Data/Http/Templates/fics Size: 41.0 KB (41,995 B) Group: phonesystem [999] v Owner: phonesystem [999] v
Cell4telNXS32-32FXS.txs.xml	phonesystem [995]   Permissions: Owner R W X Set UID   Group R W X Set GID   Others R W X Setdry bit   Octal: 0644
	OK Cancel Help

3. Upload the Call4TeINXS-ZIP File (renamed) to the 3CX Server

- Linux: /var/lib/3cxpbx/Instance1/Data/Http/Templates/fxs
- Windows: C:\ProgramData/3cxpbx/Instance1/Data/Http/Templates/fxs

Upon successful upload, the Call4Tel FXS Template can be found under Advanced --> FXS/DECT

≡	3CX						Support+ Updates +	<b>e</b> -	20.0	
-	Phones		FXS/DECT							
٥	SIP Trunks									1
4	Inbound Rules		• Autocater	A Detate						
Ť	Outbound Rules		Search							
	Messaging		Name	Brand	Model	Lines	MAC			
0	Digital Receptionists									
-	Ring Groups									
40	Call Queues									
	Backup and Restore									
-	Reporting	*								

4. Click on + Add FXS / DECT and select the correct Call4tel template for your device.

Add FXS/DECT	×	
Select Brand		
Call4tel	~	
Select model/device		12 Port FXS gateway 16 Port FXS gateway
16 Port FXS gateway		2 Port FXS gateway 24 Port FXS gateway
Mac Address		32 Port FXS gateway 4 Port FXS gateway
Mac Address		8 Port FXS gateway

For configuration steps, refer to the <u>3CX Call4Tel-FXS Configuration Guide</u>.