

RUN 3CX ON A HIGH-PERFORMANT, LOW-COST PBX APPLIANCE

Easy cloud management from anywhere

Forget about investing in a dedicated server and office space to run your 3CX. Use a cost-effective, high-performant, small-sized PBX appliance instead and get all the features with less admin.

Call4tel's PBX appliances are managed from anywhere from the cloud portal and come with 3CX V18 & Debian 10 pre-installed - all you need to do is plug them in.

- › Zero setup PBX appliance
- › Full feature set
- › Cloud Managed
- › High-performance
- › Up to 800 users
- › Anti-hacking module
- › Plug 'n' play IP Phones & SIP Trunks
- › 24/7 support

NX32 Series

NX32 Lite



Up to 200 users
32GB EMMC storage
6GB LPDDR4 RAM

NX32



Up to 100 users
32GB EMMC storage
4GB DDR3L RAM

NX32C

Customise logo and UI



Up to 100 users
32GB EMMC storage
4GB DDR3L RAM

NX256 - NX96 - NX64 AiO

NX96



Up to 200 users
1TB SSD storage
8GB DDR3 RAM

NX256



Up to 800 users
1TB SSD storage
16GB DDR4 RAM

NX256RR



Up to 1500 users
2x 1TB SSD storage
16GB DDR4 RAM
RAID Controller & Redundant PSU

NX64 AiO



Up to 200 users
32G EMMC storage
6GB LPDDR4 RAM
Support up to 8 ports FXO/FXS

Get Your Demo Today! www.call4tel.com

Sales: +6563401005 | sales@call4tel.com

Model	NX32 Lite	NX32/NX32C	NX96	NX256-i5
Users Register (recommended)	200	100	200	800
3CX Software	Preloaded v18 or higher		Preloaded v18 or higher	
Preloaded Debian OS for 3CX	Yes	Yes	Yes	Yes
Cloud Managed (Optional)	Yes	Yes	Yes	Yes
Pre loaded 3CX SBC	Yes	Yes	Yes	Yes
Processor	Dual Core Celeron	Intel Atom	Quad Core Celeron	Intel i5
RAM	6GB LPDDR4	4GB DDR3L	8GB DDR3L	16GB DDR4
Storage	32GB EMMC	32GB EMMC	1TB SSD	1TB SSD
Storage (for Call Recordings)	USB SATA (option)	USB SATA (option)	Built-in SSD	Built-in SSD
Ethernet Interface (WAN, LAN)	2x 1000Mbps	2x 100Mbps	2x 1000Mbps	2x 1000Mbps
USB Port for External Storage	2x USB 3.0	2x USB 2.0	2x USB 2.0	2x USB 3.0
HDMI port (Display)	1	1	1	1
FXO Port				
FXS Port				
Power Supply	12V/1A Adapter	12V/1A Adapter	Internal 100-240V AC	Internal 100-240V AC
Power Consumption	12W	12W	25W	100W
Certification	3CX	3CX	3CX	3CX
Size (L x W x H) mm	118 x 118 x 28	165 x 165 x 40	510 x 350 x 90	510 x 430 x 95
Weight	0.48 kg	1.3 kg	3.0 kg	4.5 kg
Working Environment	Operation Range: 0°C to 50°C; Storage Range: -20°C to 65°C; Humidity: 10-90% non-condensing			
Form Factor	Desktop	Desktop	1U Rack Mount	1U Rack Mount
Color	Blue	Black	Black	Black
Warranty	1 Year (Limited)	1 Year (Limited)	1 Year (Limited)	1 Year (Limited)
Exporting Packing (Units per carton)	10	10	3	2
Carton Size (L x W X H) mm	280 x 220 x 50	330 x 27 5x 75	530 x 460 x 320	530 x 450 x 210
Weight	6.1 kg	12.5 kg	11.0 kg	10.2kg

Model	NX256RR-i5	NX256RR-i7	NX64 AiO
Users Register (recommended)	800	1500	200
3CX Software	Preloaded v18 or higher		Preloaded v18 or higher
Preloaded Debian OS for 3CX	Yes	Yes	Yes
Cloud Managed (Optional)	Yes	Yes	Yes
Pre loaded 3CX SBC	Yes	Yes	Yes
Processor	Intel i5	Intel i7	Intel Dual Core Celeron
RAM	16GB DDR4	16GB DDR4	6GB LPDDR4
Storage	2x 1TB SSD	2x 1TB SSD	32G EMMC
Storage (for Call Recordings)	Built-in SSD	Built-in SSD	USB SATA (option)
Ethernet Interface (WAN, LAN)	3x 1000Mbps	3x 1000Mbps	2x 1000Mbps
USB Port for External Storage	2x USB 3.0	2x USB 3.0	2x USB 2.0
HDMI port (Display)	1	1	1
FXO Port			up to 8 ports
FXS Port			up to 8 ports
Power Supply	2x Internal 100-240V AC	2x Internal 100-240V AC	12V/2A Adapter
Power Consumption	100W	100W	24W
Certification	3CX	3CX	3CX
Size (L x W x H) mm	510 x 430 x 95	510 x 430 x 95	362 x 250 x 81
Weight	4.8 kg	4.8 kg	1.2KG
Working Environment	Operation Range: 0°C to 50°C; Storage Range: -20°C to 65°C; Humidity: 10-90% non-condensing		
Form Factor	1U Rack Mount	1U Rack Mount	Desktop
Color	Black	Black	Blue
Warranty	1 Year (Limited)	1 Year (Limited)	1 Year (Limited)
Exporting Packing (Units per carton)	2	2	10
Carton Size (L x W X H) mm	530 x 450 x 210	530 x 450 x 210	530 x 410 x 470
Weight	11.4 kg	11.4 kg	13.0 kg